

STIRLING[®]

Designer Collection

Espresso Machine



Quick Start Guide

Espresso machines are relatively complex appliances to use. Please read the full manual for comprehensive instructions and safety advice before first use. This Quick Start Guide only contains basic information.



Fill the tank

Fill the tank with fresh tap water. It is removable, if you prefer to fill it under the tap.



Preheat

Press the ON/OFF button to switch the machine on. Insert a filter into the porta filter, fit the porta filter to the group head and place a cup (or two) underneath the espresso outlets.

NOTE: When the HEATING light turns off, turn the function dial to the ☺ position, let some hot water flow into the cup(s) and then turn the dial back to the neutral position to switch off the pump. Let the water heat the cups and discard it just before brewing coffee.



Add coffee

Remove the porta filter, add coffee (1 measuring spoonful for 1 cup, 2 for 2 cups), press the coffee down lightly with the tamp and fit the porta filter to the group head.



Make espresso

Set the HOT WATER/STEAM selector to HOT WATER (released), place the empty, warm cup(s) underneath the outlets and when the HEATING light turns off, turn the function dial to the ☺ position. **Turn the function dial back to the neutral position when you have enough coffee in your cup(s).**



Froth milk

Fill around 100mL of cold milk into the cold stainless steel jug. Swing the steam wand to the side of the appliance and place the milk jug underneath, with the nozzle just below the surface of the milk. With the function dial set to the ☺☺ position, move the jug round for around 40-45 seconds, making sure the nozzle remains submerged. When the milk is textured to your liking, turn the function dial back to the neutral position.

For more information please visit www.stirlingappliances.com.au or call 1300 886 649

Model Number	STR-ESPM
Colour	Matte White
Warranty	3 Years
Version	QSG-V1.0